

## Nokian Noktop Pro

### Nokian Noktop 32

Width 205, 220, 230, 240, 250, 260, 275 mm

Length 3300 - 3360 mm

Pattern depth 15,0 mm

Application All season use for free rolling axles

- Medium and long haul
- Busses
- Cargo transport



#### Technical data

Order code	Width mm	Length mm	Pattern Depth mm	Kg/m	Kg/pcs	Product code
32 205	205	3360	15,0	4,0	13,4	<b>T672526</b>
32 220	220	3360	15,0	4,3	14,4	<b>T672527</b>
32 230	230	3320	15,0	4,3	14,4	<b>T672538</b>
32 240	240	3330	15,0	4,5	15,1	<b>T672539</b>
32 250	250	3315	15,0	4,7	15,6	<b>T672540</b>
32 260	260	3330	15,0	4,8	15,9	<b>T672541</b>
32 275	275	3315	15,0	5,0	16,6	<b>T672542</b>

Compound Special rubber compound

- Low heat generation and tear resistant compound reduces rolling resistance and improves overall economy

Green

- HA-oil free
- Low rolling resistance
- Excellent durability
- Production process fulfils environmental standards of ISO 14 001

Properties

- Good all-round pattern
- Strongly shaped main grooves give excellent longitudinal and lateral grip
- Uniform shoulder area and groove structure enables smooth wear and steady handling
- Self cleaning main grooves and cool running
- DSI (Driving Safety Indicator)

Alternative Noktop 72

25.6.2009